

BORON 15

Maxi Granular

PRODUCT SPECIFICATION

TYPICAL PHYSICAL PROPERTIES

Screen Analysis.....	97% Between 2.5 - 3 mm	Bulk Density.....	56 lbs. per cu. foot
Color.....	White to Light Gray	SGN (Size Guide Number).....	280
pH.....	8.0 - 8.5	Granulation.....	Prilled
Hardness.....	6.0 lbs / Granule		

TYPICAL CHEMICAL ANALYSIS

Derived from Ulexite

Typical Analysis.....	Boron (B) 14.3 to 15.0%	Lead (Pb).....	< 5 ppm
GUARANTEED Analysis.....	Boron (B) 14.3%	Mercury (Hg).....	< 0.1 ppm
Equivalent B ₂ O ₃	46.0 - 48.3%	Molybdenum (Mo).....	< 10 ppm
Arsenic (As).....	< 100 ppm	Nickel (Ni).....	< 3 ppm
Cadmium (Cd).....	< 2 ppm	Selenium (Se).....	< 1 ppm
Cobalt (Co).....	< 3 ppm		

PACKAGING OPTIONS

Multi-ply 50 lb. Bags with PE Liner (40 bags per ton pallet)
2000 lb. Polypropylene Super Bags (1 per pallet)

SHIPPING POINTS

Baltimore, MD

Moses Lake, WA

Savannah, GA

Suffolk, VA

BORON 15 FORMULATION GUIDE

Lbs./Acre of B Required	1	2	3	4	5	6
Lbs. Of BORON 15	6.7	13.4	20.1	26.7	33.4	40.0

CAMERON[®]
CHEMICALS, INC.
ESSENTIAL GRANULAR MICRONUTRIENTS

10.17.16



4530 Professional Circle, Ste.201
Virginia Beach, VA 23455
FAX: 757.487.1280

1.757.487.0656
www.cameronchemicals.com